


3200NXT



	3
	4
	6
	7
-	8
	9
	13
	21
	22
	23
2750/2850/2900	26
2750/2850/2900	27
3150/3900	28
3150/3900	29
2750/2850/3150	30
2900/3900	31
	32



CHG Change of State

CHG

INI Initializing

30-45

INI

RGQ Regeneration Queued

SRV

RGQ

SRV Service

SRV

LCK Lock

P4

LCK

4# SRV 03:45PM
REGEN IN 07 DAYS

4

4# SRV* 03:45PM

1. 4

2. 4

5#1 SRV* 03:45PM
VOLUME 1000 g

5

5#3 SRV 03:45PM
VOLUME 1000 g

5

#3

6#1 SRV* 03:45PM
SYSVOL 4000 g


6

/

CAT3 CAT5

- 1.
- 2.
- 3.


100





3200NXT


5

"D"









,

- 1. 5
- 2. 12:01PM 12:01HR 5
- 1.
- 2. "D" 5
- 25 12:00PM 12:00HR

1. SYSTEM TYPE

4 5 6 7 9

- 1.
- 2.

SYSTEM TYPE: 4
SINGLE UNIT

2. VALVE ADDRESS

1 2 3 4 #1

- 1.
- 2.

VALVE ADDRESS:
2

3. SYSTEM SIZE

1 2 3 4

- 1.
- 2.

SYSTEM SIZE:

4. REGEN TYPE

- 1.
- 2.

REGEN TYPE:
TIME CLK DELAYED

5. VALVE TYPE

- 1.
- 2.

VALVE TYPE:
2750

6. REGENERANT FLOW

- 1.
- 2.

REGENERANT FLOW:
DOWN FLOW

7. **REMOTE SIGNAL**

- 1.
- 2.

REMOTE SIGNAL
START: 00:00:00

5#1 SRV* 05:38PM
SIGNAL 00:06:00

0 6 6

8. **DISPLAY FORMAT**

- 1.
 - 2.
- 12
- 24

DISPLAY FORMAT:
US-GALLONS

9. **UNIT CAPACITY**

- 1.
 - 2.
 - 3.
- 9,000-9,900,000 300,000
- 90.0-199,000 300.0

UNIT CAPACITY:
300000 GRAINS

10. CAPACITY SAFETY

0-50% 0%

1.
2.
3.

CAPACITY SAFETY
FACTOR: 00%

11. FEED WATER HARDNESS

1-199 / 15 /
2-199 30

1.
2.
3.

FEED WATER
HARDNESS: 015 GPG

12. REGENERATION DAY

1-99 OFF

1.
2.
3.

REGENERATION DAY
OVERRIDE: OFF

REGENERATION DAY
OVERRIDE: 01 DAYS

13. REGENERATION TIME

02:00AM
02:00HR

- 1.
- 2.
- 3.

REGENERATION
TIME: 02:00AM

14. REGENERATION CYCLE STEPS

1-5

	1		2		3		4		5	
		10		1		10		12		
		1		10		10		12		
		12		1		1		10		10

15. AUXILIARY RELAY OUTPUT

16

17

AUXILIARY RELAY:
ENABLED

16. ()



17.

0-999	1-999
0.00-9.99	1-999

- 1.
- 2.
- 3.
- 4.



18. FLOW METER

- 1.0" 2750
- 1.5" 2850/2900
- 2.0" 3150
- 3.0" 3900

- 1.0"
- 1.5"

•


- 1.
- 2.
- 3.



FLOW METER:

19. MAXIMUM FLOW

- 1.
- 2.
- 3.



MAXIMUM FLOW
RATE: 0000 GPM


20.

- 1.
- 2.
- 3.




ADD 01 GALLONS

21.



PROGRAMMING UNIT
PLEASE WAIT...

5



6

1. —
2. —
3. —
4. —
5. —

5


1. "D"

2.

3.

"D"

4.



"D"

"D"

- 1" 75gpm(.28m³/m)
- 1.5" 90gpm(.34m³/m)
- 2" 175gpm(.66m³/m)
- 3" 350gpm(1.32m³/m)
- 1" 1.5" 75gpm

CURRENT FLOW
RATE: 0 gpm

PEAK FLOW RATE:
0.00m

- 1.
- 2.

5

CURRENT FLOW
RATE: 0 gpm

LAST TWO REGENS:
0000 HOURS

LAST REGEN:
0000 HOURS

6

- 1.
- 2.
- 3.


VOLUME REMAINING
TANK: 00000000 g

6

VOLUME REMAINING
SYS: 0000000000 g

2

VALVE ADDRESS:
2





2750/2850/2900

Item No.	Quantity	Part No.	Description
1.....			
6.....	5.....	10302.....	insulator, limit switch
7.....	3.....	10218.....	switch, micro
8.....	2.....	10231.....	screw, slot hex, 1/4 - 20 x 1/2
9.....	1.....	41544.....	motor, drive, 24V, 50/60 Hz
10.....	1.....	12777.....	cam, sh
		41049.....	transformer, euro, 230V/24V 108VA
		41050.....	transformer, aust, 230V/24V, 108VA
13.....	1.....	10691.....	plug, 750 dia, recessed, black
17.....	1.....		
		19121-09	meter cable assy, NT, 99.5" w/connector
27.....	1.....	00217-02.....	cover assy, 2900, lower, black, environmental
28.....	1.....	18626.....	spacer, indicator
29.....	1.....	18746.....	bearing, co
34.....	1.....	11381.....	pin, roll, 2900/3900
35.....	1.....	14759.....	link, piston rod
36.....	1.....	14769.....	bracket, motor, 2900
37.....	1.....	14775.....	cam, drive, 2900
40.....			
41.....			

3150/3900

Item No.	Quantity	Part No.	Description
1	1	19304-04	backplate, 3150/3900
2	1	15120	bracket
8	4	10218	switch, micro
9	2	16047	
16	3	11774	ring, retaining
17	2	16047	link, drive
18	2	11709	pin, drive link
19	1	16048	bearing, drive link
20	2	11805	screw, rd hd, 4-40 x 5/8, type 1
33	1	40941	wire harness
37	1	14202-01	screw, hex wsh, 8-32 x 5/16
38	1	17421	plug, 1.20 hole
39	2	60240-02	cover assy, 3150/3900, env, black
40	1	40392	motor, drive, 115V, 50/60Hz
45	1	16048	bearing, drive link
46	2	11805	screw, rd hd, 4-40 x 5/8, type 1
47	1	16495	cam assy, 3900, l


2750/2850/3150



- T1-24V
- VDM-
- SW1-
- SW2-
- SW3-
- HCAM-
- SCAM-
- BVCAM-
- FM- ()
- M1- ()
- S1-

2900/3900

42148_REV C



DETECTED ERROR=

1.

#1

DETECTED ERROR=
NO MESSAGE #1

1.

2.

3.

#1

DETECTED ERROR=

1.

2.

3.

#3

#3

DETECTED ERROR=

1.

#1

DETECTED ERROR=

1.

DETECTED ERROR=
MATCHING ADDRESS

1.

A.	A.
B.	B.
C. ()	C.
D. ()	D.
E. ()	E.